



Spray plan completed by: _____

Sprayer Set Up Record / Sprayer Operation Procedure

Operator	Spray Hub Plan		
Description of rig	Gold Acres G4		
Location, Date		Oct-25	
Product or products	Xtendimax Dicamba		
Target pest(s)			
Droplet size recommendation per label or agronomist	XC-VC		
Water rate l/ha (minimum recommended)	100	L/ha	
Determine:			
Minimum speed you wish to	8	km/hr	
Constant speed you wish to	18	km/hr	
Maximum speed you wish to	21	km/hr	
Boom nozzle spacing (W) in metres	0.5	metre	
Total boom width	36.5	metre	
No. of nozzles on boom	73	nozzles	
Litres per minute per nozzle = km/hr x W (nozzle spacing in metres) x litres/ha ÷ 600 L/min/nozzle			
Minimum	Constant	Maximum	Refer to nozzle chart record selections
0.67	1.50	1.75	Nozzle Siz Pressure
			• • • • •
Nozzle code selected		SELECT	SELECT
		TTI11001	TTI11002 YELLOW
Droplet Size			
Pressure range			



Total No. of Nozzles _____

Combination of Nozzles		
3TS	Nozzle 1 Quantity 73	Nozzle 2 Quantity 74
Dual Line	Line A	Line B
Spray quality		

W = nozzle spacing (in metres)
for broadcast sprayingor W = spray width (in metres) for single
nozzle brand spraying or boomless
sprayingor W = row spacing (in metres) divided by
the number of nozzles per row for
directed spraying

	Tier 1			Tier 2			Tier 3		
	Minimum	Constant	Maximum	Minimum	Constant	Maximum	Minimum	Constant	Maximum
Spray quality as per ISO 25358	XC	VC	VC	XC	VC	VC	XC	XC	VC
Pressure as per nozzle chart	4	5	6	4	5	6	3	4	5
Litres per minute/nozzle	0.68	0.76	0.83	0.91	1.02	1.12	1.38	1.59	1.78
Duty cycle %									

Step 2 Kilometres/hour

= Litres per minute per nozzle x 600 ÷ litres sprayed hectare ÷ width (nozzle spacing in metre)

Speed km/h	8.16	9.12	9.96	10.92	12.24	13.44	16.56	19.08	21.36
------------	------	------	------	-------	-------	-------	-------	-------	-------

Litres/hectare

= Litres per minute per nozzle x 600 ÷ width (nozzle spacing in metres) ÷ kilometre

Litres/hectare	100	100	100	100	100	100	100	100	100
----------------	-----	-----	-----	-----	-----	-----	-----	-----	-----

Final Check**Sprayer Operation Rules**

Pressure 1 bar = 100 kpa = 14.5psi

Panel Settings	Tier 1			Tier 2			Tier 3		
Total litres per minute all nozzles	49.64	55.48	60.59	67.34	75.48	82.88	100.74	116.07	129.94
Litres/minute/nozzle x number of nozzles									
Speed km/h	8.16	9.12	9.96	10.92	12.24	13.44	16.56	19.08	21.36
Pressure in bar	4	5	6	4	5	6	3	4	5
Spray quality as per ISO 25358	XC	VC	VC	XC	VC	VC	XC	XC	VC